



9 MM



15 + 1 RND



4.28"



AMBI

DANIEL H9

Get more control for faster, flatter shooting with the DANIEL H9. With the thinnest profile and lowest bore axis in its class, the DANIEL H9 is designed and engineered to make you a better shooter.

While sharing the ergonomics, pointability, and straight-pull trigger with the classic 1911, the DANIEL H9 has all the features demanded of a modern striker-fired handgun. It features ambidextrous controls, accessory rail and is optics-ready. The aircraft-grade aluminum grip keeps the DANIEL H9 surprisingly lightweight and ensures the legendary durability you have come to expect from Daniel Defense—all built around a cold hammer forged barrel.

It's the future of defense—built in Black Creek, GA—by the most trusted name in firearms.

FEATURES:

- + Low Bore Axis For Less Muzzle Rise & Faster, More Accurate Follow-Up Shots
- + Straight-Pullback Trigger & Trigger Safety Blade For Precision Control & Improved Safety
- + One-Piece-Machined Ambidextrous Slide Stop & Reversible Mag-Release Button For Superior Ergonomics
- + Cold Hammer Forged Barrel, 1:10 Twist, 6 Groove, Polygonal Rifling
- + Type 7075 Aluminum Grip For Less Weight and More Strength
- + Balanced-Texture Grip Panels For Comfort & Secure Purchase
- + Compatible with Most Popular Red Dot Optics
- + Slim Profile For Optimal Maneuverability & Concealability
- + Steel Factory Sights With Dovetail Cut
- + Low Friction Magazine Finish for Smooth Insertion/Removal

SPECIFICATIONS:

Model	DANIEL H9
Caliber	9x19 MM
Action	Striker-Fired, Reciprocating Slide, Tilting Barrel
Magazine Capacity	15 Rounds
Barrel Length	4.28"
Overall Length	7.69"
Overall Height	5.12"
Overall Width	1.2" (Slide Stops)
Slide Width	1.0"
Weight	29.6 oz. (Unloaded Magazine)
Accessory Rail	STANAG 4694
Sights	Fixed: Fiber Optic Front, Black-Out Rear – U-Notch
Safety Devices	Trigger Safety Blade, Trigger Safety Plunger, Striker Block
Trigger Type	Metal Construction, Straight Pull w/Integral Safety Blade

PRODUCT

Daniel H9, Compact

MANUFACTURING

50-179-23095